COFFEE BREWING SYSTEMS

CBS-2260 NG Brewers

3.0-3.5 GALLON BREWING SYSTEM

Shown with **D012 12.0L / 3.0G LUXUS® Thermal Dispenser**




CAPACITIVE TOUCHSCREEN DISPLAY

The NG line features a capacitive LED touchscreen display. Set brew times, program recipe buttons and more with just the touch of a finger. It's as easy as a smartphone.



LED STATUS BAR

Quickly identify where your machine is at in the brewing process from anywhere in the room. The LED Status Bar changes color during the brewing process to let you know when it's ready to brew, brewing, almost done and ready to serve.



BREW BASKET LOCKS

Brew baskets lock in place during the brewing process for added safety and quality control.

FETCO®

FEATURES

CBS-2260 NG Brewers



BREW BASKET DESIGN

Advanced brew basket design provides a deeper bed depth and superior therma insulation for better extraction.



CASCADING SPRAY DOME

Patented design provides even saturation of the coffee bed for maximum extraction. Lime resistant design makes for less service calls.



ECO MODE

Reduces tank temperature during periods of non-operation to cut down on electricity usage.

COLOR OPTIONS

STAINLESS STEEL FINISH



MATTE BLACK FINISH



MATTE WHITE FINISH



DISPENSERS

CBS-2260 NG Brewers

DISPENSERS

D012

12.0 Liter / 3.0 Gallon
LUXUS® Thermal
Dispenser
TPD-30

NSF



All dispensers **SOLD SEPARATELY**.

ACCESSORIES

CBS-2260 NG Brewers

BREW BASKETS AND PAPER FILTERS

Item Number	Brew Basket	Coffee Capacity	Filter Size	Filter SKU	Filter/Case
All configurations	Stainless Steel	Up to 32oz / 907g	20" x 8"	F004	500/cs

B00828004

21" x 7"
Stainless Steel
Brew Basket

B00828005

21" x 7"
Stainless Steel
Brew Basket
with Clips



F004

20" x 8"
Paper Filters



Contact Customer Service or your Sales Person for more options.

WATER FILTRATION SYSTEM

Filtration System	Item Number	Item Description	Rated Capacity	Working Pressure	Weight
Everpure®	A161	In-Line System	113,563 liters	10-125 psi [0.7-8.6 bar], non-shock	6.0 lbs / 2.7 kg
Everpure®	A075	Replacement Cartridge	113,563 liters	10-125 psi [0.7-8.6 bar], non-shock	6.0 lbs / 2.7 kg
BWT Bestmax	A138	In-Line System	3,002 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A139	Replacement Cartridge	3,002 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A140	In-Line System	4,562 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A141	Replacement Cartridge	4,562 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg

EVERPURE®

In-Line Water
Filtration System



SET INCLUDES: 1ea. commercial quality corrosion resistant filter head 1ea. taste and odor filter cartridge (FETCO® #A075) | 1ea. 3/8" x 4' connection hose | 1 set — mounting bracket and hardware.

- Recommended for large-sized operations
- Taste and odor filter for extremely turbid (cloudy) water
- Granular-activated carbon reduces sediment and chlorine
- Quick-disconnect style head/cartridge design cartridge for effortless replacement
- Durable, corrosion-resistant head inlcudes built-in shutoff valve

BWT BESTMAX

In-Line Water
Filtration System



SET INCLUDES: 1ea. filter cartridge | 1ea. universal filter head | 1ea. wall mounting bracket

- Recommended for small- to medium-sized operations
- Carbonate hardness removal prevents scale deposits and retains minerals
- Granular-activated carbon reduces sediment and chlorine
- Quick-disconnect style head/cartridge design cartridge for effortless replacement
- Durable, corrosion-resistant head inlcudes built-in shutoff valve
- Four bypass settings allows for different water qualities and product preferences
- Optional braided hose supplies 3/8" and 3/4" compression, in 24" or 48" lengths

TECHNICAL SPECIFICATIONS

NORTH AMERICA

CBS-2261 NG Brewer

ELECTRICAL

Item Number	Color	Brew Basket	Voltage	Heater Configuration	Ph.	Wires	kW	Connection	Max Amp Draw	[Gal]/[L] / Hour	Certification
E2261US-UB230-MA110 **DUAL PHASE**	Stainless Steel	21x7" Metal	208-240 208-240	2 x 3.0 kW / 240 V 3 x 3.0 kW / 240 V	1 3	2+G 3+G	4.6-6.1 6.9-9.1	No Cord No Cord	22.1-25.4 19.2-22.1	15.9 / 60.4 23.9 / 90.6	

WATER

Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	1.50 / 5.68	8.63 / 32.67

CBS-2262 NG Brewer

ELECTRICAL

Item Number	Color	Brew Basket	Voltage	Heater Configuration	Ph.	Wires	kW	Connection	Max Amp Draw	[Gal]/[L] / Hour	Certification
E2262US-3B330-MA110	Stainless Steel	21x7" Metal	208-240	3 x 3.0 kW / 240 V	3	3+G	6.9-9.1	No Cord	19.2-22.1	23.9 / 90.6	
E2262US-3B630-MA110	Stainless Steel	21x7" Metal	208-240	6 x 3.0 kW / 240 V	3	3+G	13.6-18.1	No Cord	37.5-43.7	31.9 / 120.8	
E2262US-3B340-MA110	Stainless Steel	21x7" Metal	208-240	6 x 4.0 kW / 240 V	3	3+G	6.9-9.1	No Cord	25.5-29.3	47.8 / 181.3	
E2262US-3B640-MA110	Stainless Steel	21x7" Metal	208	6 x 4.0 kW / 240 V	3	3+G	18.1	No Cord	50.4	47.8 / 181.3	

WATER

Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	3.00 / 11.36	15.86 / 60.04

1 This version is made to order and it might require longer production lead time. Please ask your local sales representative for more information.

TECHNICAL SPECIFICATIONS

INTERNATIONAL

CBS-2261 NG Brewer

ELECTRICAL

Item Number	Brew Basket	Voltage	Heater Configuration	Ph.	Wires	kW	Connection	Max Amp Draw	[Gal]/[L] / Hour	Certification
E2261IN-3C330-MA110	21x7" Metal	220/380-240/415	3 x 3.0 kW / 240 V	3	3L/N/PE	7.7-9.1	No Cord	11.9-12.9	23.9 / 90.6	NSF, cULus
E2261IN-3C340-MA110	21x7" Metal	220/380-240/415	3 x 4.0 kW / 240 V	3	3L/N/PE	10.2-12.1	No Cord	15.7-17.1	30.0 / 113.7	NSF, cULus
E2261IN-3C350-MA110[1]	21x7" Metal	220/380-240/415	3 x 5.0 kW / 240 V	3	3L/N/PE	12.7-15.1	No Cord	19.6-21.3	30.0 / 113.7	NSF, cULus
E2261NM-3B350-MA110	21x7" Metal	208-240	3 x 5.0 kW / 240 V	3	3+G	11.4-15.1	No Cord	31.7-36.5	30.0 / 113.7	NSF, NOM
E2261CE-3C330-MA110	21x7" Metal	230/400	3 x 3.0 kW / 240 V	3	3L/N/PE	8.4	No Cord	12.3	22.1 / 83.6	NSF, CE
E2261CE-3C340-MA110	21x7" Metal	230/400	3 x 4.0 kW / 240 V	3	3L/N/PE	11.1	No Cord	16.3	29.2 / 110.8	NSF, CE

WATER

Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	1.50 / 5.68	8.63 / 32.67

CBS-2262 NG Brewer

ELECTRICAL

Item Number	Brew Basket	Voltage	Heater Configuration	Ph.	Wires	kW	Connection	Max Amp Draw	[Gal]/[L] / Hour	Certification
E2262IN-3C350-MA110[1]	21x7" Metal	220/380-240/415	3 x 5.0 kW / 240 V	3	3L/N/PE	12.7-15.1	No Cord	19.6-21.3	39.9 / 151.1	NSF, cULus
E2262IN-3C630-MA110	21x7" Metal	220/380-240/415	6 x 3.0 kW / 240 V	3	3L/N/PE	15.2-18.1	No Cord	23.4-25.4	47.8 / 181.3	NSF, cULus
E2262NM-3B630-MA110	21x7" Metal	208-240	6 x 3.0 kW / 240 V	3	3+G	13.6-18.1	No Cord	37.9-43.7	47.8 / 181.3	NSF, NOM
E2262CE-3C340-MA110	21x7" Metal	230/400	3 x 4.0 kW / 240 V	3	3L/N/PE	11.1	No Cord	16.3	29.2 / 110.8	NSF, CE
E2262CE-3C350-MA110	21x7" Metal	230/400	3 x 5.0 kW / 240 V	3	3L/N/PE	13.9	No Cord	20.3	36.7 / 139.0	NSF, CE

WATER

Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	3.00 / 11.36	15.86 / 60.04

1 This version is made to order and it might require longer production lead time. Please ask your local sales representative for more information.
2 Based on standard (factory) settings: 6.0 minute brew time (0% prewet; 93°C water), DT=140°F, 3 gallon per batch.

DIMENSIONS

CBS-2261 NG Brewer

DIMENSIONS

	Height (A)	Width (B)	Depth (D)	Depth (E)	Brew Basket Clearance (F)	Faucet Clearance (G)
Product Dimensions	41.38" 105.11 cm	17.88" 45.42 cm	27.50" 69.85 cm	22.25" 56.52 cm	23.88" 60.66 cm	12.13” 30.80 cm
Shipping Dimensions	39.0" 99.06 cm	23.0" 58.42 cm	28.0" 71.72 cm	N/A	N/A	N/A

WEIGHT

	Empty [lbs] / [kg]	Filled [lbs] / [kg]
Product Weight	88 lbs 39.9 kg	160 lbs 72.6 kg
Shipping Weight	97 lbs 44.0 kg	N/A

CBS-2262 NG Brewer

DIMENSIONS

	Height (A)	Width (C)	Depth (D)	Depth (E)	Brew Basket Clearance (F)	Faucet Clearance (G)
Product Dimensions	41.38" 105.11 cm	32.0" 81.28 cm	27.50" 69.85 cm	22.25" 56.52 cm	23.88" 60.66 cm	12.13” 30.80 cm
Shipping Dimensions	39.0” 99.06 cm	37.0" 93.98 cm	29.0" 73.66 cm	N/A	N/A	N/A

WEIGHT

	Empty [lbs] / [kg]	Filled [lbs] / [kg]
Product Weight	130 lbs 59.0 kg	266 lbs 120.7 kg
Shipping Weight	140 lbs 63.5 kg	N/A



1 On/Off
2 USB
3 Power
4 Water

FETCO®

WEBSITE
fetco.com

EMAIL
inquiries@fetco.com

PHONE
+1.847.719.3000
1.800.338.2699

FAX
+1.847.719.3001

ADDRESS
FETCO®
600 Rose Road
Lake Zurich, IL 60047, USA

© Copyright 2026 FETCO® is a mark of Food Equipment Technologies Company.
Dispensers, airpots, paper filters, water filters, stands, accessories and options sold separately

Rev. 1.0 2026.06.29 Digital Letter