

KOLD-DRAFT

STILL THE ONLY CUBE OF ITS KIND.

COCKTAIL SERIES

KD-50E, KD-70E, KD-110E

THE COCKTAIL SERIES

Produces premium Cocktail Cubes (1" x 1" x 1 1/4") for top-shelf beverages, with premium cube quality and a slower melt rate.



KD-50E



KD-70E



KD-110E

Cocktail Series Daily Capacities: Lbs of Ice per 24 Hours per Unit

Model Number	Electrical Volts/Hz/Ph	Condenser	Ice Capacity 24 Hours lbs (kg)		Storage Capacity lbs (kg)	Energy Input 90°F (32°C) 70°F (21°C) kWh/100 lbs (kJ/kg)	Water Use gal/100lb (l/kg)		Min. Circuit Amp	Max. Fuse Size Amps
			70°F (21°C) 50°F (10°C) Ambient/Water	90°F (21°C) 70°F (10°C) Ambient/Water			90°F (32°C) / 70°F (21°C) Potable	Condenser		
KD-50E	115/60/1	Air	59 (27)	56 (25)	26.5 (12)	9.69 (769)	22.3 (1.9)	N/A	5	15
KD-70E	115/60/1	Air	82 (37)	68 (31)	40 (18)	8.43 (669)	23 (1.9)	N/A	5	15
KD-110E	115/60/1	Air	118 (54)	111 (50)	60 (27)	7.04 (559)	15.6 (1.3)	N/A	7	15

Dimensions/Weight (with 6" Legs)

Model Number	Dimensions W x D x H	Ship Weight
KD-50E	15.5" x 17.7" x 36.7" (39.4cm x 45cm x 93.2cm)	95lb (43kg)
KD-70E	19.7" x 17" x 36.7" (50cm x 43.2cm x 93.2cm)	110lb (50kg)
KD-110E	24.8" x 20.7" x 36.7" (63cm x 52.6cm x 93.2cm)	130lb (59kg)

Recommended Operating Requirements

Description	Minimum	Maximum
Room Temperature	45°F (7°C)	90°F (32°C)
Water Temperature	45°F (7°C)	90°F (32°C)
Voltage 115	104V	126V
Potable Water Pressure	20 PSIG (137 kPa)	100 PSIG (689 kPa)

Plumbing:

1/4" Hose
Drain

Exterior Finish:

300 Series Stainless Steel

Refrigeration System:

R290 Refrigerant

Clearance Requirements:

Front Must Be Completely Unobstructed
at Least 4" Clearance on the Back, and
.06" Clearance for the Top and Sides



Cocktail Cube
1" x 1" x 1.25"



KOLD-DRAFT

101 Corporate Woods Parkway, Vernon Hills, IL 60061
1-800-840-9577 | info@kold-draft.com | www.kold-draft.com



KD SS COCKTAIL 01-26