

KOLD-DRAFT


STILL THE ONLY CUBE OF ITS KIND.



SC201 SERIES SELF CONTAINED ICE MACHINE

KOLD-DRAFT SC201

- Produces Unique 1.25" x 1.25" x 1.25" Hard, Square Cubes
- Slow Melting Cube Perfect for Cocktails and Beverages
- Stores 125 lbs of Ice
- ADA Compliant - 31.4" H Without Legs, Fits Under 34" Countertops
- Ideal for Any Undercounter or Bar Application
- Front Breathing Design Allows for Installation in Tight Spaces



Big Cube
1.25" x 1.25" x 1.25"

SC201 Series Daily Capacities: Lbs of Ice per 24 Hours per Unit

Model Number	Electrical Volts/Hz/Ph	Condenser	Ice Capacity 24 Hours lbs (kg)		Energy Input 90°F (32°C) 70°F (21°C) kWh/100lbs (kJ/kg)	Water Use gal/100lb (l/kg)		Min. Circuit Amp	Max. Fuse Size Amps
			70°F (21°C) Ambient/Water	90°F (21°C) 70°F (10°C) Ambient/Water		90°F (32°C) Potable	70°F (21°C) Condenser		
SC201ACE	115/60/1	Air	158 (71)	133 (60)	5.98 (474.4)	33.0 (2.75)	N/A	6.1	15

Dimensions/Weight

Description	Dimensions W x D x H	Ship Weight
Air Cooled (Without Legs)	26" x 28.6" x 31.4" (66cm x 72.6cm x 79.8cm)	207lb (94kg)
Air Cooled (With Legs)	26" x 28.6" x 37.4" (66cm x 72.6cm x 100cm)	207lb (94kg)

Recommended Operating Requirements

Description	Minimum	Maximum
Room Temperature	45°F (7°C)	110°F (43°C)
Water Temperature	45°F (7°C)	90°F (32°C)
Voltage 208-230	198V	253V
Voltage 115	104V	126V
Potable Water Pressure	5 PSIG (0.034 kPa)	100 PSIG (689 kPa)

Plumbing:

1/2" FIP Potable Water Inlet
3/4" FIP Ice Bin Drain
1/2" FIP Ice Maker Drain
.88" Diameter Electrical Connection

Refrigeration System:

Thermostatic Expansion Valve Controlled
R290 Refrigerant

Exterior Finish:

Corrosion-Resistant Stainless
Steel Exterior with Plastic Door
and Bin Liner



KOLD-DRAFT

101 Corporate Woods Parkway, Vernon Hills, IL 60061
1-800-840-9577 | info@kold-draft.com | www.kold-draft.com



KD SS SC201 01-26