



190 SERIES

Undercounter Ice Cube Machine

UYP0190A | UDP0190A | UYP0190AX



ICE SHAPES



▶ **Half-Dice:** 3/8" x 1 1/8" x 7/8"
(0.95 x 2.86 x 2.22 cm)



▶ **Dice:** 7/8" x 7/8" x 7/8"
(2.22 x 2.22 x 2.22 cm)

SIZE

- ▶ Up to 200 lbs (91 kgs) of daily ice production
- ▶ 26" (66.0 cm) wide, 28.50" (72.4 cm) deep, and 38.50" (97.8 cm) high on 6" (15.24 cm) legs
- ▶ 3.4 ft³ (0.096 m³) cabinet volume
- ▶ 80 lbs (36.3 kgs) ice storage capacity*

*Application capacity based on
90% volume x 33 lbs./ft³ average density of ice

SPECIFICATIONS

Refrigerant: R290

- ▶ Air-cooled: 4.94 oz (140 g)

BTU Per Hour:

- ▶ Air-cooled:
 - 3,200 (average)
 - 3,800 (peak)

Compressor: Nominal rating 0.5 Hp

Operating Limits:

- ▶ Ambient temperature range: 50° to 100°F (10° to 37.7°C)
- ▶ Water temperature range: 45° to 90°F (4.4° to 32.2°C)
- ▶ Water pressure ice maker
 - ◆ Water in
 - Min. 20 psi (137.9 kPa)
 - Max. 80 psi (551.1 kPa)

Power:

115/60/1 (230/50/1 available) 115/60/1 ice machines are factory pre-wired with an 8 ft (243 cm) power cord and NEMA 5-15P-plug configuration. 208-230/50/1 ice machines are factory pre-wired with an 8 ft (243 cm) power cord only, no plug installed

- ▶ Minimum circuit ampacity
 - Air-cooled 115V: 6 amps
- ▶ Maximum fuse size
 - 115V: 15 amps
 - HACR-type circuit breakers can be used in place of fuses

FEATURES



Touchpad

Easy to read and use touchpad - on/off, delay/repeat, clean, filter, full bin, service indicator



Onboard Water Filtration

Integrated water filtration enhances performance and ice quality; replacement filters available in 5-micron (K00530) and 0.5-micron (K00531)



Air Flow / Installation

Front ventilation is ideal for installation under countertops or next to other equipment

Optional floor-sealing configuration with legs not installed, remains front-serviceable



Removable Bin

Removable, forward-sliding storage bin allows for easy access to refrigeration components for cleaning and maintenance

NEO[®] 190 SERIES

Undercounter Ice Cube Machine


UYP0190A | UDP0190A | UYP0190AX

INSTALLATION

Ice machine must be installed indoors.

Recommended clearance for the top, side, and back is 5" (12.7 cm). No minimum clearance is required.

- A 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet
- B 1/2" (1.27 cm) F.P.T. Ice Making Water Drain
- C 1/2" (1.27 cm) F.P.T. Bin Water Drain
- D Electrical Entrance



SPECIFICATIONS

Air Cooled						@ 90° Air/70°F Water (32° Air/21°C Water)			
	Model	Ice Shape	Shipping Weight	Ice Production 24 Hours		Power Usage kWh per 100 lbs of Ice		Ice Machine Potable water usage per 100 lbs Ice	Condenser Water Usage per 100 lbs Ice
				70°Air/50°F Water 21°Air/10°C Water	90°Air/70°F Water 32°Air/21°C Water	1 ph	3 ph		
	UYP0190A	Half-Dice	153 lbs (69 kgs)	200 lbs (91 kgs)	180 lbs (82 kgs)	5.83 ★	n/a	15.5 gal (58.67 L)	n/a
	UDP0190A	Dice	153 lbs (69 kgs)	200 lbs (91 kgs)	175 lbs (79 kgs)	5.83 ★	n/a	15.5 gal (58.67 L)	n/a
	UYP0190AX*	Half-Dice	153 lbs (69 kgs)	200 lbs (91 kgs)	169 lbs (77 kgs)	6.36 ★	n/a	15.5 gal (58.67 L)	n/a

Standard 6" (15.24 cm) adjustable leg and standard plastic NEO ice scoop included.
*Factory-installed LuminIce II. If factory installed LuminIce II is not available use LuminIce II kit part number K00519.
★ Energy Star Model

Limited Commercial Warranty
Ice Maker Three (3) years parts and labor
Evaporator Five (5) years parts and labor
Compressor Five (5) years parts, three (3) years labor



2110 South 26th Street | Manitowoc, WI 54220 | United States
+1.920.682.0161 | 920.683.7589 Fax | manitowocice.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners. ©2025 Pentair. All rights reserved.

