

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Sandwich / Salad Unit

Food Prep Tables
M3 Series

Model: MST-72



NO MAINTENANCE REQUIRED

___ FEATURES & BENEFITS =__

- Self-cleaning condenser device Only at Turbo Air
 - The accumulation of dust in the condenser causes the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products in refrigerators. The self-cleaning condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.
- Cold air compartment

Our innovative "Cold Air Compartment" maintains temperature evenly for each pan to preserve fresh food longer. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

Stainless steel cabinet construction

The Turbo Air M3 model boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides and back. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined setting.

■ Hot gas condensate system Only Turbo Air models

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

- 9-1/2" deep, 1/2" thick cutting board included with convenient side rail
- Insulated pan cover
- Efficient refrigeration system

Turbo Air's M3 solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Refrigerator holds 33°F ~ 39°F for the best in food preservation











Model	Swing Door	CU./FT.	#of Shelves	#of Pans	#of Hood	НР	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
MST-72	3	19	3	18	2	1/2	9.9	374	725/8 x 30 x 37

(unit: inch)

Sandwich / Salad Unit

Model: MST-72

ELECTRICAL DATA						
Voltage	115/60/1					
Plug Type	(i) NEMA 5-15P					
Full Load Amperes	9.9					
Compressor HP	1/2					
Cord Length (ft.)	9					
Refrigerant	R-134A					
DIMENSIONAL DATA						
Ext. Length Overall (in.)	725/8 (1844mm)					
Ext. Depth Overall (in.) *	30 (762mm)					
Ext. Height Overall (in.) †	37 (940mm)					
# of Doors	3					
# of Shelves	3					
# of Pans	18					
Net Capacity (cu. ft.)	19					
Net Weight (lbs.)	325					
Gross Weight (lbs.)	374					
Shelf Size (in.)	21 x 17 (Left/Right)					
311011 3120 (III.)	23 x 17 (Middle)					

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

■ WARRANTY: 3 Year Parts and Labor Warranty **Additional 2 Year Warranty on Compressor**


- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Standard 1/6 size, 4" deep condiment pans included
- 2.5" dia. casters available (optional) & Legs available (optional)
- Removable food covers available (optional)
- Stainless steel double overshelf available (optional)

■ OPTIONAL ACCESSORIES :


- ☐ 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" ABS plastic leg: 30221M0200
- ☐ 6" stainless steel leg: 30221M0600
- ☐ Additional PE coated wire shelf: WM77800100 (Left/Right), WM77800300 (Middle)
- ☐ Removable food cover: RCT-72-L (Left) / RCT-72-R (Right)
- ☐ Stainless steel double overshelf: TSOS-6R
- Door lock: extra lead time will apply, please call factory for more details to order
- External digital thermometer: extra lead time will apply, please call factory for more details to order

Ver.201606

PLAN VIEW



PLAN VIEW



SIDE VIEW


























^{*} Depth does not include 1" for rear spacers.

[†] Height does not include 5" for caster height.