

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Undercounter Refrigerator

Undercounters M3 Series

Model: MUR-36





NO MAINTENANCE REQUIRED

___ FEATURES & BENEFITS =__

■ Self-cleaning condenser device Only at Turbo Air

The accumulation of dust in the condenser causes the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products in refrigerators. The self-cleaning condenser device keeps the condenser clean and prevents system

Stainless steel cabinet construction

The Turbo Air M3 model boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides and back. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined setting.

■ Efficient refrigeration system

failure by automatically brushing daily.

M3's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

■ Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Refrigerator holds 33°F ~ 38°F for the best in food preservation











ENERGY STAR® Qualified

Model	Swing Door	CU./FT.	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H [†] (inches)
MUR-36	2	9.5	2	1/4	6.6	199	361/4 x 30 x 305/8

(unit: inch)

Undercounter Refrigerator

Model: MUR-36

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	① NEMA 5-15P				
Full Load Amperes	6.6				
Compressor HP	1/4				
Cord Length (ft.)	9				
Refrigerant	R-134A				
DIMENSIONAL DATA					
Net Capacity (cu. ft.)	9.5				
Ext. Length Overall (in.)	361/4 (921mm)				
Ext. Depth Overall (in.)*	30 (762mm)				
Ext. Height Overall (in.)†	30 _{5/8} (777mm)				
# of Doors	2				
# of Shelves	2				
Net Weight (lbs.)	184				
Gross Weight (lbs.)	199				
Shelf Size (in.)	15 x 17				

Design and specifications subject to change without notice

Actual shipping weight may differ due to extra packing materials for product protection.


■ WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- 2.5" caster available (optional)
- Legs available (optional)
- Back splash guard available (optional)
- Stainless steel double overshelf available (optional)


■ OPTIONAL ACCESSORIES :

- ☐ 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" ABS plastic leg: 30221M0200
- ☐ 6" stainless steel leg: 30221M0600
- ☐ Additional PE coated wire shelf: WM37800100
- ☐ Back splash guard: TU-36B
- ☐ Stainless steel double overshelf: TSOS-3R
- Door lock: extra lead time will apply, please call factory for more details to order
- External digital thermometer: extra lead time will apply, please call factory for more details to order

PLAN VIEW



PLAN VIEW



SIDE VIEW

Ver.201601












ENERGY STAR® Qualified

■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519 ■ Warranty: 800-381-7770 ■ AC: 888-900-1002













^{*} Depth does not include 1" for rear spacers.

[†] Height does not include 5" for caster height.