

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :	
Model #:	
Item #:	Qty:
Available W/H :	
Approval :	

# Roll-In Solid Door Refrigerator

Reach-In Top Mount Pro Series

Model: PRO-26R-RI

### 

#### ■ Self-cleaning condenser device Only at Turbo Air

The accumulation of dust in the condenser causes the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products in refrigerators. The self-cleaning condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

#### Digital temperature control & monitor system

- · Keep food products safe by maintaining constant temperatures.
- Alarms that sound when doors are not sealed shut; protect against food spoilage that originate from cold air leaks.
- · Digital display allows for easy monitoring.
- Programs interpret the condition of refrigeration systems by self-diagnosis.
- · Automatic evaporator fan motor delays.

### All stainless steel cabinet construction

The Turbo Air Pro model boasts all stainless steel interior and exterior (galvanized steel top, bottom and back). It guarantees the utmost in cleanliness and long product life. The Pro model can add a touch of style to the most refined setting.

#### ■ Hot gas condensate system Only Turbo Air models

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but thoroughly prevents the overflow of condensate water.

- Cold air distribution system
- Door pressure release device

#### Efficient refrigeration system

Pro Series's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

#### High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- LED interior lighting
- Top mount compressor
- Refrigerator holds 33°F ~ 38°F for the best in food preservation















Model	Swing Door	CU./FT.	#of Rack Accepted	HP	AMPS	Crated Weight (lbs.)	L x D*x H † (inches)
PRO-26R-RI	1	40	1	1/3	6	410	341/8 x 377/8 x 837/8

(unit: inch)

# Roll-In Solid Door Refrigerator

## Model: PRO-26R-RI

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	(i) NEMA 5-15P			
Full Load Amperes	6			
Compressor HP	1/3			
Feed Wires with Ground	3			
Cord Length (ft.)	9			
Refrigerant	R-134A			
DIMENSIONAL DATA				
# of Doors	1			
# of Racks Accepted	1			
Net Capacity (cu. ft.)	40			
Ext. Length Overall (in.)	34 <sub>1/8</sub> (866mm)			
Ext. Depth Overall (in.) *	377/8 (960mm)			
Ext. Height Overall (in.)	837/8 (2128mm)			
Int. Length Overall (in.)	31 (787mm)			
Int. Depth Overall (in.)	31 <sub>1/2</sub> (800mm)			
Int. Height Overall (in.)	67 (1702mm)			
Net Weight (lbs.)	380			
Gross Weight (lbs.)	410			
Rack Size (L x D x H) (in.)	27 x 29 x 66			


Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


# 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

- Door locks standard
- Self-contained system
- Solid and sturdy grille design
- Heavy duty stainless steel ramp standard

### **PLAN VIEW**



**TOP VIEW** 



**FRONT VIEW** 

Ver.201606









■ **Turbo Air**: 800-627-0032

■ **GK**: 800-500-3519

■ Warranty: 800-381-7770

■ **AC**: 888-900-1002











<sup>\*</sup> Depth does not include 1-1/8" for door handles. Depth does not include 6-1/4" for ramp.