

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H:		
Approval:		

# Glass / Mug Chillers

Underbar Equipment Super Deluxe Series

**Model: TBC-50SD/SB-GF** 





TBC-50SD-GF



TBC-50SB-GF

## \_\_\_ FEATURES & BENEFITS =\_\_

#### ■ Equipped with easy-to-clean Air Filter

The accumulation of dust in the condenser causes failures and/or breakdowns in refrigeration. Refrigeration operate normally until they accumulate a certain amount of dust. When they reach over their limit, performance will drop rapidly, resulting in damages and possible disposal of stored goods. This is why all refrigeration manufacturers require the condenser to be cleaned at least once a month for warranty to remain valid. Fortunately for Turbo Air, this process is simplified due to the frontal access air filter device. Users only need to pull out the filter and vacuum lightly to remove the dust. Simply place it back into position when complete.

#### ■ Efficient refrigeration system

Turbo Air's refrigerators are designed with oversized and balanced R-404A (CFC Free) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

#### Stainless steel cabinet construction

Super Deluxe (SD) models boast a stainless steel exterior (except galvanized steel back and bottom). SB models are attractive wear-resistant black vinyl exterior. Heavy gauge stainless steel countertop and glide lids are perfect for sanitation and durability. Interior is stainless steel except galvanized steel top. Turbo Air glass chiller model guarantees utmost in cleanliness and long product life. It also can add a touch of style to the most refined setting.

#### ■ High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

#### ■ Forced air cooling system

Positive guided forced air cooling system chills dry glasses & plates fast throughout the cabinet.

#### Heavy duty, PE(Polyethylene) coated shelves Heavy duty 10mm thick pure grade PE coated adjustable shelves are provided for maximum storage use.

- Huge capacity cooler cabinet requires only minimum floor space
- Bottom mount compressor unit
- Glass / mug chiller holds 5°F ~ -5°F for the best in chilling glasses and plates











Model	Sliding Door	CU./FT.	Capacity 8" Mug / 10oz Stein	# of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
TBC-50SD-GF	2 2	15	140 / 386 Cups	5	1/2	9.0	280	50 x 261/2 x 331/4
TBC-50SD-GF		15	140 / 386 Cups	5	1/2	9.0	280	50 x 261/2 x 331/4

(unit: inch)

# Glass / Mug Chillers

## **Model: TBC-50SD/SB-GF**

ELECTRICAL DATA						
Voltage	115/60/1					
Plug Type	① NEMA 5-15P					
Full Load Amperes	9.0					
Compressor HP	1/2					
Refrigerant	R-404A					
Cord Length (ft.)	8.5					
DIMENSIONAL DATA						
Capacity (8" Mug / 10oz Stein)	140 Cups / 386 Cups					
Net Capacity (cu. ft.)	15					
Ext. Length Overall (in.)	50 (1270mm)					
Ext. Depth Overall (in.)*	261/2 (673mm)					
Ext. Height Overall (in.)†	331/4 (845mm)					
Net Weight (lbs.)	240					
Gross Weight (lbs.)	280					
# of Shelves	5					

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


## ■ WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


- Self-contained system
- 4" dia. swivel casters standard
- 2" dia. casters available (optional)
- 6" height adjustable legs available (optional)


#### ■ OPTIONAL ACCESSORIES :

- ☐ 2" caster for underbar series, ½" diameter: P0165B0100 (non-brake), P0165B0110 (w/ brake)
- ☐ 6" adjustable stainless steel leg: P012P0100

### **PLAN VIEW**







SIDE VIEW

Ver 201601



















■ **Turbo Air**: 800-627-0032

■ **Warranty**: 800-381-7770



■ **GK**: 800-500-3519

■ AC: 888-900-1002

<sup>\*</sup> Depth does not include 2" for cap catcher or 2" for rear spacers.

<sup>†</sup> Height does not include 5" for caster height.