

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval:		

Bottle Coolers

Underbar Equipment Super Deluxe Series

Model: TBC-80SD/SB





Easy to Clean Air Filter
Front Access

___ FEATURES & BENEFITS =__

■ Equipped with easy-to-clean Air Filter

The accumulation of dust in the condenser causes failures and/or breakdowns in refrigeration. Refrigeration operate normally until they accumulate a certain amount of dust. When they reach over their limit, performance will drop rapidly, resulting in damages and possible disposal of stored goods. This is why all refrigeration manufacturers require the condenser to be cleaned at least once a month for warranty to remain valid. Fortunately for Turbo Air, this process is simplified due to the frontal access air filter device. Users only need to pull out the filter and vacuum lightly to remove the dust. Simply place it back into position when complete.

■ Efficient refrigeration system

Turbo Air's refrigerators are designed with oversized and balanced R-134A (CFC Free) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

- Forced air cooling system
- Positive guided forced air cooling system chills bottles on top first.

Stainless steel cabinet construction

Super Deluxe (SD) models boast a stainless steel exterior (except galvanized steel back and bottom). SB models are attractive wear-resistant black vinyl exterior. Heavy gauge stainless steel countertop and glide lids are perfect for sanitation and durability. Interior is stainless steel except galvanized steel top. Turbo Air Bottle Cooler model guarantees utmost in cleanliness and long product life. It also can add a touch of style to the most refined setting.

■ High-density polyurethane insulation

TBC-80SB

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

- Adjustable, heavy duty, PE (polyethylene) coated dividers
- Rugged built-in removable bottle cap opener and cap catcher
- Huge capacity cooler cabinet requires only minimum floor space
- Side mount compressor unit

By positioning the compressor on the side of the unit, refrigerators can now be serviced without being moved. Our innovative, front breathing feature also allows this model to provide high efficiency in narrow spaces.

 Refrigerator holds 33°F ~ 38°F for the best in beverage preservation











Model	Sliding Door	CU./FT.	Capacity 12oz.btls. / 12oz.cans	# of Dividers	НР	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
TBC-80SD TBC-80SB	3 3	22.6 22.6	30.8 / 43.2 Cases 30.8 / 43.2 Cases	5 5	1/2 1/2	9	378 378	801/2 x 261/2 x 331/4 801/2 x 261/2 x 331/4

(unit: inch)

Bottle Coolers

Model: TBC-80SD/SB

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type					
Full Load Amperes	9				
Compressor HP	1/2				
Refrigerant	R-134A				
Cord Length (ft.)	8.5				
DIMENSIONAL DATA					
Capacity (12oz.btls./12oz.cans)	30.8 Cases / 43.2 Cases				
Net Capacity (cu. ft.)	22.6				
Ext. Length Overall (in.)	801/2 (2044mm)				
Ext. Depth Overall (in.)*	261/2 (673mm)				
Ext. Height Overall (in.)†	331/4 (845mm)				
Net Weight (lbs.)	345				
Gross Weight (lbs.)	378				
# of Dividers	5				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


■ WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


- Self-contained system
- 4" dia. swivel casters standard
- 2" dia. casters available (optional)
- 6" height adjustable legs available (optional)

■ OPTIONAL ACCESSORIES:


- ☐ 2" caster for underbar series, ½" diameter: P0165B0100 (non-brake), P0165B0110 (w/ brake)
- ☐ 6" adjustable stainless steel leg: P012P0100

PLAN VIEW





FRONT VIEW



Ver.201603













■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

SIDE VIEW

■ Warranty: 800-381-7770 ■ AC: 888-900-1002











^{*} Depth does not include 2" for cap catcher or 2" for rear spacers.

[†] Height does not include 5" for caster height.