

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval:		

# Pizza Prep Table - Drawers

Food Prep Tables - Pizza Prep Super Deluxe Series

**Model: TPR-44SD-D2** 



 Each drawer accommodates up to 6" deep sixth (1/6) size pans (drawer pans not included)



#### **NO MAINTENANCE REQUIRED**

#### == FEATURES & BENEFITS ==\_

#### ■ Self-cleaning condenser device Only at Turbo Air

The accumulation of dust in the condenser causes the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products in refrigerators. The self-cleaning condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

#### Cold air curtain system

Our innovative forced air system allows cold air to flow all around the food pan area, covering not only underneath the pan, but also to the front, top and the rear. This unique air flow creates a cold air-shield around the pan, which maintains the food temperature under 41°F (NSF requirement) even when the lids are opened.

#### Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior, exterior (galvanized steel back & bottom) and durable stainless steel drawers. It guarantees the utmost in cleanliness and long product life. The Super Deluxe can add a touch of style to the most refined setting.

#### Front breathing, side mount compressor unit

By positioning the compressor on the side of the unit, refrigerators can now be serviced without being moved. Our innovative, front breathing feature also allows this model to provide high efficiency in narrow spaces.

#### Efficient refrigeration system

Turbo Air's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

- Insulated pan cover
- Extra deep cutting board included (19-1/4" deep and 1/2" thick)

#### Excellent cooling system

Powerful, forced-air refrigeration system maintains the storage cabinet at a constant temperature. The evaporator fan and a newly designed stainless steel louver allow uniform distribution of cold air to the food pans and throughout the unit to keep food temperature within the NSF standard 7 requirements.

#### High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

# ■ Refrigerator holds 33°F ~ 41°F for the best in food preservation











Model	Swing Door	Drawers	CU./FT.	#of Shelves	#of Pans	HP	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
TPR-44SD-D2	-	2	14	1	6	1/4	6.3	321	44 x 321/4 x 36

(unit: inch)

## Model: TPR-44SD-D2

ELECTRICAL DATA						
Voltage	115/60/1					
Plug Type	(i) NEMA 5-15P					
Full Load Amperes	6.3					
Compressor HP	1/4					
Cord Length (ft.)	9					
Refrigerant	R-134A					
DIMENSIONAL DATA						
Ext. Length Overall (in.)	44 (1118mm)					
Ext. Depth Overall (in.)*	321/4 (819mm)					
Ext. Height Overall (in.)†	36 (914mm)					
# of Doors	-					
# of Shelves	-					
# of Pans	6					
Net Capacity (cu. ft.)	14					
Net Weight (lbs.)	266					
Gross Weight (lbs.)	321					

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


### ■ WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Standard 1/3 size, 6" deep condiment pans included (top of cabinet)
- 2.5" dia. casters available (optional)
- Legs available (optional)
- Stainless steel single overshelf available (optional)


#### OPTIONAL ACCESSORIES :

- ☐ 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" ABS plastic leg: 30221M0200
- $\square$  6" stainless steel leg: 30221M0600
- ☐ Stainless steel single over-shelf: TSOS-P4
- External digital thermometer: extra lead time will apply, please call factory for more details to order

### **PLAN VIEW**



**PLAN VIEW** 



SIDE VIEW

Ver.201602





















■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519 ■ Warranty: 800-381-7770 ■ AC: 888-900-1002

<sup>\*</sup> Depth does not include 3" for cutting boards and 1" for rear spacers. † Height does not include 5" for caster height.