

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

# **Undercounter Freezer** - Drawers

Undercounters Super Deluxe Series

**Model: TUF-28SD-D2** 



 Each drawer accommodates up to 6" deep sixth (1/6) size pans (drawer pans not included)



NO MAINTENANCE REQUIRED

#### \_\_\_ FEATURES & BENEFITS =\_\_

### ■ Self-cleaning condenser device Only at Turbo Air

The accumulation of dust in the condenser causes the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products in refrigerators. The self-cleaning condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

#### Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe can add a touch of style to the most refined setting.

#### Efficient refrigeration system

Turbo Air's solid door freezers are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster freezing and greater efficiency.

### ■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

#### Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

 Freezer holds 0°F ~ -10°F for the best in frozen food preservation











Model	Swing Door	Drawers	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D*x H <sup>†</sup> (inches)
TUF-28SD-D2	-	2	7	-	1/3	5.3	169	271/2 x 30 x 305/8

(unit: inch)

## Model: TUF-28SD-D2

ELECTRICAL DATA						
Voltage	115/60/1					
Plug Type	① NEMA 5-15P					
Full Load Amperes	5.3					
Compressor HP	1/3					
Cord Length (ft.)	9					
Refrigerant	R-134A					
DIMENSIONAL DATA						
Net Capacity (cu. ft.)	7					
Ext. Length Overall (in.)	27 <sub>1/2</sub> (699mm)					
Ext. Depth Overall (in.)*	30 (762mm)					
Ext. Height Overall (in.)†	305/8 (777mm)					
# of Doors	-					
# of Shelves	-					
Net Weight (lbs.)	152					
Gross Weight (lbs.)	169					

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection


■ WARRANTY: 3 Year Parts and Labor Warranty
Additional 2 Year Warranty on Compressor

- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- 2.5" caster available (optional)
- Legs available (optional)
- Back splash guard available (optional)


#### ■ OPTIONAL ACCESSORIES:

- ☐ 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" ABS plastic leg: 30221M0200
- ☐ 6" stainless steel leg: 30221M0600
- ☐ Back splash guard: TU-28B
- External digital thermometer: extra lead time will apply, please call factory for more details to order

### **PLAN VIEW**



**PLAN VIEW** 



Ver.201601














■ Warranty: 800-381-7770 ■ AC: 888-900-1002











<sup>\*</sup> Depth does not include 1" for rear spacers. † Height does not include 5" for caster height.