

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Undercounter Freezer - Drawers

Undercounters Super Deluxe Series

Model: TUF-48SD-D2



- Each drawer accommodates up to 6" deep sixth (1/6) size pans (drawer pans not included)

NO MAINTENANCE REQUIRED

■ Self-cleaning condenser device Only at Turbo Air

The accumulation of dust in the condenser causes the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products in refrigerators. The self-cleaning condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe can add a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving Only Turbo Air models

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

■ Efficient refrigeration system

Turbo Air's solid door freezers are designed with oversized and balanced (CFC Free R-404A) refrigeration systems. These include efficient evaporators and condensers for faster freezing and greater efficiency.

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

■ Freezer holds 0°F ~ -10°F for the best in frozen food preservation











Model	Swing Door	Drawers	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D*x H [†] (inches)
TUF-48SD-D2	1	2	12	1	1/2	8.3	253	481/4 x 30 x 305/8

(unit: inch)

Model: TUF-48SD-D2

ELECTRICAL DATA

Voltage	115/60/1					
Plug Type	① NEMA 5-15P					
Full Load Amperes	8.3					
Compressor HP	1/2					
Cord Length (ft.)	9					
Refrigerant	R-404A					
DIMENSIONAL DATA						
Net Capacity (cu. ft.)	7					
Ext. Length Overall (in.)	481/4 (1226mm)					
Ext. Depth Overall (in.)*	30 (762mm)					
Ext. Height Overall (in.)†	305/8 (777mm)					
# of Doors	1					
# of Shelves	1					
Net Weight (lbs.)	231					
Gross Weight (lbs.)	253					
Shelf Size (in.)	21 x 17					

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- 2.5" caster available (optional)
- Legs available (optional)
- Back splash guard available (optional)
- Stainless steel double overshelf available (optional)


OPTIONAL ACCESSORIES :

- ☐ 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" ABS plastic leg: 30221M0200
- ☐ 6" stainless steel leg: 30221M0600
- ☐ Additional stainless steel shelf: M727800100
- ☐ Back splash guard: TU-48B
- ☐ Stainless steel double overshelf: TSOS-4R
- External digital thermometer: extra lead time will apply, please call factory for more details to order

PLAN VIEW



PLAN VIEW



Ver 201601






















^{*} Depth does not include 1" for rear spacers.

[†] Height does not include 5" for caster height.