

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Worktop Freezer

Worktops Super Deluxe Series

Model: TWF-28SD





NO MAINTENANCE REQUIRED

___ FEATURES & BENEFITS =__

■ Self-cleaning condenser device Only at Turbo Air

The accumulation of dust in the condenser causes the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products in refrigerators. The self-cleaning condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe can add a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving
 Only Turbo Air models

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

■ Efficient refrigeration system

Turbo Air's solid door freezers are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster freezing and greater efficiency.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

- LED interior lighting
- Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

■ Freezer holds 0°F ~ -10°F for the best in frozen food preservation











ENERGY STAR®

Qualified

Model	Swing Door	CU./FT.	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H [†] (inches)
TWF-28SD	1	7	1	1/3	5.3	175	271/2 x 30 x 331/2

(unit: inch)

Model: TWF-28SD

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	(i) NEMA 5-15P				
Full Load Amperes	5.3				
Compressor HP	1/3				
Cord Length (ft.)	9				
Refrigerant	R-134A				
DIMENSIONAL DATA					
Net Capacity (cu. ft.)	7				
Ext. Length Overall (in.)	27 _{1/2} (699mm)				
Ext. Depth Overall (in.) *	30 (762mm)				
Ext. Height Overall (in.)†	331/2 (851mm)				
# of Doors	1				
# of Shelves	1				
Net Weight (lbs.)	157				
Gross Weight (lbs.)	175				
Shelf Size (in.)	221/2 x 17				

Design and specifications subject to change without notice

Actual shipping weight may differ due to extra packing materials for product protection.


■ WARRANTY: 3 Year Parts and Labor Warranty **Additional 2 Year Warranty on Compressor**

- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- 2.5" caster available (optional)
- Legs available (optional)


OPTIONAL ACCESSORIES :

- ☐ 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" ABS plastic leg: 30221M0200
- ☐ 6" stainless steel leg: 30221M0600
- ☐ Additional stainless steel shelf: M277800100
- Door lock: extra lead time will apply, please call factory for more details to order
- External digital thermometer: extra lead time will apply, please call factory for more details to order

PLAN VIEW



PLAN VIEW



SIDE VIEW

Ver.201601











ENERGY STAR® Qualified

■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519













^{*} Depth does not include 1" for rear spacers. † Height does not include 5" for caster height.